

# Product datasheet

Specifications



## Circuit breaker, ComPact NSX250H, 70kA/415VAC, TMD trip unit 200A, 3 poles 3d

LV431671

❗ Discontinued on: 15 Jun 2023

❗ Discontinued

**Important message:** This product has been switched to new ComPacT range and is no longer commercialized.  
EAN Code: 3606480014475

### Main

Range	ComPact
Product name	ComPact NSX
Range of product	ComPact NSX100...250
Device short name	NSX250H
Product or component type	Circuit breaker
Device application	Distribution
Number of poles	3P
Protected poles description	3t
[In] rated current	200 A at 40 °C
[Ue] rated operational voltage	690 V AC 50/60 Hz
Network type	AC
Network frequency	50/60 Hz
Suitability for isolation	Yes conforming to EN/IEC 60947-2
Utilisation category	Category A

[Icu] rated ultimate short-circuit breaking capacity  
85 kA at 240 V AC 50/60 Hz conforming to UL 508  
65 kA at 480 V AC 50/60 Hz conforming to UL 508  
10 kA Icu at 660/690 V AC 50/60 Hz conforming to IEC 60947-2  
100 kA Icu at 220/240 V AC 50/60 Hz conforming to IEC 60947-2  
35 kA Icu at 525 V AC 50/60 Hz conforming to IEC 60947-2  
50 kA Icu at 500 V AC 50/60 Hz conforming to IEC 60947-2  
65 kA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2  
70 kA Icu at 380/415 V AC 50/60 Hz conforming to IEC 60947-2  
15 kA at 600 V AC 50/60 Hz conforming to UL 508

Performance level	H 70 kA 415 V AC
Trip unit name	TM-D
Trip unit technology	Thermal-magnetic
Trip unit protection functions	LI
Control type	Toggle
Circuit breaker mounting mode	Fixed

### Complementary

[Ui] rated insulation voltage	800 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV

<b>[Ics] rated service short-circuit breaking capacity</b>	10 kA at 660/690 V AC 50/60 Hz conforming to IEC 60947-2 100 kA at 220/240 V AC 50/60 Hz conforming to IEC 60947-2 35 kA at 525 V AC 50/60 Hz conforming to IEC 60947-2 50 kA at 500 V AC 50/60 Hz conforming to IEC 60947-2 65 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2 70 kA at 380/415 V AC 50/60 Hz conforming to IEC 60947-2
<b>Mechanical durability</b>	20000 cycles
<b>Electrical durability</b>	5000 cycles at 690 V In 10000 cycles at 690 V In/2 10000 cycles at 440 V In 20000 cycles at 440 V In/2
<b>Mounting support</b>	Backplate
<b>Upside connection</b>	Front
<b>Downside connection</b>	Front
<b>Connection pitch</b>	35 mm
<b>Protection type</b>	L : for overload protection (thermal) I : for short-circuit protection (magnetic)
<b>Trip unit rating</b>	200 A at 40 °C
<b>Long-time pick-up adjustment type <math>I_r</math> (thermal protection)</b>	Adjustable
<b>[<math>I_r</math>] long-time protection pick-up adjustment range</b>	0.7...1 x In
<b>Long-time protection delay adjustment type <math>t_r</math></b>	Fixed
<b>[<math>t_r</math>] long-time protection delay adjustment range</b>	120...400 s at 1.5 x In 15 s at 6 x $I_r$
<b>Short-time protection pick-up adjustment type <math>I_{sd}</math></b>	Adjustable
<b>[<math>I_{sd}</math>] Short-time protection pick-up adjustment range</b>	5...10 x In
<b>Short-time protection delay adjustment type <math>t_{sd}</math></b>	Fixed
<b>Earth-leakage protection</b>	Without
<b>Number of slots for electrical auxiliaries</b>	5 slot(s)
<b>Width (W)</b>	105 mm
<b>Height (H)</b>	161 mm
<b>Depth (D)</b>	86 mm
<b>Net weight</b>	2.4 kg

## Environment

<b>Standards</b>	EN/IEC 60947
<b>Product certifications</b>	CCC Marine EAC
<b>Overvoltage category</b>	Class II
<b>Electrical shock protection class</b>	Class II
<b>Pollution degree</b>	3 conforming to IEC 60664-1
<b>IP degree of protection</b>	IP40 conforming to IEC 60529
<b>IK degree of protection</b>	IK07 conforming to IEC 62262
<b>Ambient air temperature for operation</b>	-25...70 °C
<b>Ambient air temperature for storage</b>	-50...85 °C

---

<b>Relative humidity</b>	0...95 %
<b>Operating altitude</b>	0...2000 m without derating 2000 m...5000 m with derating

---

## Packing Units

---

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	14.0 cm
<b>Package 1 Width</b>	11.0 cm
<b>Package 1 Length</b>	19.0 cm
<b>Package 1 Weight</b>	1.99 kg
<b>Unit Type of Package 2</b>	S04
<b>Number of Units in Package 2</b>	12
<b>Package 2 Height</b>	30.0 cm
<b>Package 2 Width</b>	40.0 cm
<b>Package 2 Length</b>	60.0 cm
<b>Package 2 Weight</b>	24.646 kg

---

## Contractual warranty

---

<b>Warranty</b>	18 months
-----------------	-----------



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Total lifecycle Carbon footprint	629
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

### Use Better

#### Materials and Substances

<a href="#">EU RoHS Directive</a>	Compliant with Exemptions
SCIP Number	3874e08b-fcb8-4aa9-87c4-d36abebf2833

### Use Again

#### Repack and remanufacture

End of life manual availability	<a href="#">End of Life Information</a>
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins