

# Product datasheet

Specifications



## Multi9 - OC contact - 1 OF - 240/415 V AC - 24/130 V DC

M9A26924

 Discontinued on: 1 Sept 2023

 Discontinued

### Main

range of product	Multi9
Product or component type	OC contact
Device short name	OF
Signal contacts composition	1 C/O
[In] rated current	3 A at 415 V, AC 50/60 Hz 6 A at <= 240 V, AC 50/60 Hz
[Uc] control circuit voltage	240...415 V AC 50/60 Hz 24...130 V DC
9 mm pitches	1
Standards	EN/IEC 60947-5-1 EN 62019-2
Product certifications	CSA UR UL CCC PCT

### Complementary

[Ui] rated insulation voltage	500 V
[Uimp] rated impulse withstand voltage	4 kV
Mounting mode	Fixed
Mounting support	DIN rail
Comb busbar and distribution block compatibility	Top: YES
Height	85 mm
Width	9 mm
Depth	73.5 mm
Net weight	0.03 kg
Connections - terminals	Clamp terminal (bottom) 1 cable(s) 2.5 mm <sup>2</sup> (AWG 14) - rigid Clamp terminal (bottom) 2 cable(s) 1.5 mm <sup>2</sup> (AWG 16) - rigid
Wire stripping length	9 mm for bottom connection
Tightening torque	1 N.m bottom

### Environment

Ambient air temperature for operation	-25...50 °C
---------------------------------------	-------------

---

Ambient air temperature for storage -40...85 °C

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.1 cm
Package 1 Width	8 cm
Package 1 Length	9.5 cm
Package 1 Weight	37 g
Unit Type of Package 2	BB1
Number of Units in Package 2	12
Package 2 Height	8.5 cm
Package 2 Width	10 cm
Package 2 Length	26.5 cm
Package 2 Weight	512 g
Unit Type of Package 3	S03
Number of Units in Package 3	108
Package 3 Height	30 cm
Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	5.009 kg



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

## Use Better

### Materials and Substances

[EU RoHS Directive](#)

Compliant

SCIP Number

28bfb466-f950-4025-8655-16cfe4e6c6f3

REACH Regulation

[REACH Declaration](#)

## Use Again

### Repack and remanufacture

End of life manual availability

[End of Life Information](#)

WEEE Label

 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins