


Product data sheet

Specifications



Legend panel 200x100mm template 1, Harmony XB5

ZBYLEG201001

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Product or Component Type	Legend panel
Accessory / separate part category	Marking accessories
Complementary	
Material	Plastic
Device Composition	Marked panel
Accessory / separate part destination	<ul style="list-style-type: none">Ø 16 mm control and signalling unitsØ 22 mm control and signalling unitsØ 30 mm control and signalling unitsFor standard head
Range Compatibility	Harmony XB4 Harmony XB5 Harmony XB6 Harmony 9001K
Legend holder size	200 x 100
Net Weight	0.022 lb(US) (0.010 kg)

Environment

Standards	ISO 21702 ISO 22196:2011
-----------	-----------------------------

Ordering and shipping details

Category	US10CS222467
Discount Schedule	0CS2
GTIN	3606489755706
Returnability	Yes
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	0.20 in (0.5 cm)
Package 1 Width	8.66 in (22.0 cm)
Package 1 Length	8.66 in (22.0 cm)
Package weight(Lbs)	2.1 oz (60.0 g)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACH Regulation	REACH Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Again

Repack and remanufacture

Take-back	No
-----------	----

Offer Marketing Illustration

Product benefits / Features

Technical Benefits

Harmony XB5

Conformity with IEC, UL, CSA, CCC EAC, and JIS standards, as well as CE marking and marine approvals



Operating temperature from -40°C to 70°C

Up to IP66, 67, 69, 69K, and type 4X protection ratings



Shock protection level up to IK06

High vibration resistance with shake-proof terminal screws

Secure switching of inductive or heavy DC loads directly – 100 000 operations at 10A, 24V dc

Offer Marketing Illustration

Product benefits / Features

Features

Harmony XB5



-  Quick and easy assembly and disassembly
-  Excellent mechanical connection with operator head
-  Various types of connection: screw clamp, connector, Faston connector, spring terminal, or printed circuit board
-  Large set of accessories to customize your panels
-  Robustness to withstand harsh environments

Image of product / Alternate images

Alternative





