

Product data sheet

Specifications



Undervoltage release (MN), TeSys Deca, 220-240V AC 50 Hz

GVAU225

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range	TeSys TeSys Deca
Product or Component Type	Undervoltage release
Device short name	GVAU

Complementary

Range compatibility	TeSys GV2ME TeSys GV2LE TeSys GV2L TeSys GV2P TeSys GV3L TeSys GV3P TeSys Deca
[Uc] control circuit voltage	220...240 V AC 50 Hz
Control circuit voltage limits	0.85...1.1 Un
[Ui] rated insulation voltage	690 V AC IEC 60947-1 600 V AC UL 60947-4-1 600 V AC CSA C22.2 No 60947-4-1
Threshold tripping voltage	0.7...0.35 Un
Inrush power in VA	12 VA AC
Inrush power in W	8 W
Hold-in Power Consumption in VA	3.5 VA AC
Hold-in power consumption in W	1.1 W
Operating time	10...15 ms IEC 60947-1
On-load factor	100 %
Connections - terminals	screw clamp terminals 1 0.002...0.004 in ² (1...2.5 mm ²)solid screw clamp terminals 2 0.002...0.004 in ² (1...2.5 mm ²)solid screw clamp terminals 1 0.001...0.004 in ² (0.75...2.5 mm ²)flexible without cable end screw clamp terminals 2 0.001...0.004 in ² (0.75...2.5 mm ²)flexible without cable end screw clamp terminals 1 0.001...0.002 in ² (0.75...1.5 mm ²)flexible with cable end screw clamp terminals 2 0.001...0.002 in ² (0.75...1.5 mm ²)flexible with cable end
Tightening torque	< 1.4 N.m screw clamp terminals
Mechanical durability	10000 cycles with GV3P and GV3L 30000 cycles with GV2ME and GV2P
Quantity per Set	Set of 10
Height	3.5 in (89 mm)
Width	0.7 in (18 mm)
Depth	2.6 in (66 mm)
Net Weight	0.231 lb(US) (0.105 kg)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

color	Dark grey
-------	-----------

Ordering and shipping details

Category	US10I1122367
Discount Schedule	0111
GTIN	3389110345995
Returnability	No
Country of origin	CZ

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	1.496 in (3.800 cm)
Package 1 Width	3.346 in (8.500 cm)
Package 1 Length	3.740 in (9.500 cm)
Package weight(Lbs)	3.810 oz (108.000 g)
Unit Type of Package 2	S02
Number of Units in Package 2	42
Package 2 Height	5.906 in (15.000 cm)
Package 2 Width	11.811 in (30.000 cm)
Package 2 Length	15.748 in (40.000 cm)
Package 2 Weight	10.754 lb(US) (4.878 kg)

Contractual warranty

Warranty	18 months
----------	-----------



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic Yes

[EU RoHS Directive](#) Compliant

REACH Regulation [REACH Declaration](#)

California proposition 65
WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](#)

Use Again

Repack and remanufacture

Circularity Profile [End of Life Information](#)

Take-back No

WEEE Label The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Connections and Schema

GVAU...



Technical Illustration

Assembly's dimensions

